

Fusing

NH Fuse Switch Disconnectors

Up to 630A

Functions

NH fuse switch disconnectors are used on low voltage electrical systems that require high protection against shortcircuit while securing on load circuit disconnection and isolation.

According to standards

- IEC/EN 60 947-3
- VDE 0660 / part 100
- IEC/EN 60 269-2-1
- VDE 0636 / part 201

Base

Manufactured out of re-inforced fiber glass with high thermal stability and self extinguishing halogen free synthetic materials. Copper contacts are galvanic surface coated. Contact springs are made of stainless steel. Symmetrical switch suitable for bottom / top cable terminal connections.

Cover

The switch operating cover consists of re-inforced fiber glass and self extinguishing thermoplastic halogen free material. Supplied with large windows which enable fuse link indicator to be clearly seen. Ergonomic handle for easy operation.



Part No.	Size	Max. Current Rating
713	NH00	160A
733	NH1	250A
743	NH2	400A
753	NH3	630A

General Purpose NH Fuses

80 to 630A (Grey) are designed to protect installations and equipment against overload and short-circuit currents on low voltage electrical circuits.

Gawe gG NH fuses are rated at 500V AC and 440V DC.

Part No.	Size	Current Rating
66920080	NH00	80
66920100	NH00	100
66920125	NH00	125
66920160	NH00	160
67120200	NH1	200
67120250	NH1	250
67220315	NH2	315
67220355	NH2	355
67220400	NH2	400
67320500	NH3	500
67320630	NH3	630

